

SDI Cable

217 Knickerbocker Ave, Bohemia, NY 11716
Tel: 631-392-1701 Fax: 631-392-1702

Alarm Cable-unshielded

Product Construction

Conductor:

Annealed Solid or stranded bare copper

Insulation:

PVC

Color code: see chart below

Jacket:

PVC (color optional)

Suitable for use from -20°C to +75°C

Every 2 feet sequential marking

Include ripcord

Applications:

Power-limited control circuits

Wiring of following systems:

Intercom

Security

Audio

Background music

Suggested voltage rating: 300V

Compliances:

UL Type CMR

Color Code Chart

No. of Cond.	Color
1	Black
2	Red
3	White
4	Green

Part No.	Description	NO. of Con	AWG Siz	Solid/Stranded	Nom. Insulation Dia.	Nom. Jacket Dia. Mm
AW22-2SLCU	Alarm Wire 22/2 Solid 1000ft UL CMR Whit	2	22	Solid	1.04	3
AW22-4STC	Alarm Wire 22/4 Stranded 1000ft UL CMR	4	22	stranded	1.04	3.2
AW22-4SLCU	Alarm Wire 22/4 Solid 1000ft UL CMR Whit	4	22	Solid	1.04	3.2
AW18-2STC	Alarm Wire 18/2 Stranded 1000ft UL CMR	2	18	stranded	1.42	3.96
AW18-4STC	Alarm Wire 18/4 Stranded 1000ft UL CMR	4	18	stranded	1.42	4.75

Cable printing:

Communication Cable - Security / Alarm Part No. *AWG/*C (UL) E230635 CMR SUN RES (quality tracking NO) 002FT—****FT

for example of AW22-2SLCU

Communication Cable - Security / Alarm AW22-2SLCU 22AWG/2C (UL) E230635 CMR SUN RES (quality tracking NO) 002FT—****FT

Package:

easy pull box