



217 Knickerbocker Ave. Bohemia, NY 11716
Tel: 631--392-1701/ 516-806-5166 Fax: 631-392-1702

Specification of Cat5e CCU

Center conductor: **0.51mm CCU, Cat5e**

Dielectric: **0.93mm**

Shielding:

Attenuation Values

Conductor:

Insulation material: **HP-PE**

Outer Jackets:**5.05**

Voltage rating: **2.5KV**

Pairs:

Nominal overall diameter:**5.10mm**

Reference Documents: **COMMSCOPE STANDARD**

UL Listed Specifications:

Standards:

Environmental Characteristics:

Temperature Rating:**20**

Installation:**FLUKE**

Operations:**QC**

Maximum installation tension: **2.5KV**

Minimum bending radius:**41**

Nominal cable weight:**3.1Kg/100m**

Nominal cable diameter:**5.10mm**

Electrical Parameters:

Mutual Capacitance:

Capacitance Unbalance: **200pF / Km**

Velocity of Propagation. **< = 0.62**

Max. Conductor D.C.R:**224**

Max. DCR Unbalance: **1.5%**

Max. Delay Skew:

Characteristic Impedance:**100+/-15 OMHS**

Cat5e Cable

- Category 5 Enhanced Cable
- 1000ft Pull box
- CCA(Copper Clad Aluminum)
- 4 Pairs / 24AWG
- Up to 350MHz
- UL Listed (E321263)
- ISO9001
- White/Blue/Grey/Orange

Frequency (MHz)	SRL dB/100 m	Return Loss dB	Attenuation dB/100 m	NEXT dB	PS-NEXT dB
	Minimum	Minimum	Maximum	Minimum	Minimum
1	23.0	20.0	2.0	70.3	68.3
4	23.0	23.0	4.1	61.2	59.2
10	23.0	25.0	6.4	55.2	53.3
16	23.0	25.0	8.1	52.2	50.2
20	23.0	25.0	9.1	50.7	48.7
31.25	21.1	23.6	11.4	47.8	45.8
62.5	18.1	21.5	16.4	43.3	41.3
100	16.0	20.1	21.0	40.3	38.3
155	14.1	18.8	26.8	37.4	35.4
200	13.0	18.0	31.0	35.7	33.7
300	11.2	16.8	39.2	33.1	31.1
350	10.6	16.3	43	32.1	30.1

PS-ACR	
n	dB/100 m
n	Minimum
	66.3
	55.2
	46.8
	42.0
	39.5
	34.2
	24.4
	16.3
	7.4
	1.4

Mutual Capacitance:	14 pF/ft nominal
Capacitance Unbalance:	330 pF/ft maximum
Velocity of Propagation:	70%
Max. Conductor D.C.R.:	28.6 ohm/1000 feet
Max. DCR Unbalance:	3%
Max. Delay Skew:	18 ns/100 m
Temperature Rating:	
- Installation:	0°C to 50°C
- Operation:	-10°C to 60°C
Maximum installing tension:	25 lb
Minimum bending radius:	1.0 inch
Nominal cable weight:	15 lb/1000 feet

Nominal cable diameter:	0.185 inch
-------------------------	------------